3M[™] Automotive Window Film CR90 Technical Data

Product Benefits

- Breakthrough multilayer nanotechnology
- Metal-free design with no electronic interference*
- Much less reflectivity than traditional window films
- Advanced heat rejection capability
- Up to 99.9% UV protection (up to SPF 1000+)
- 99% infrared light rejected**

Product Performance & Technical Data

<u>CR90</u>	Ĭ			
	Single Pane		Single Pane (Auto)	
Film	1/4" Clear	CR90	1/4" Clear Auto	CR90
Solar Heat Gain Coefficient	0.82	0.66	0.59	0.54
Visible Light Transmitted	89%	86%	75%	72%
Visible Light Reflected Interior	9%	10%	7%	9%
Visible Light Reflected Exterior	8%	10%	7%	8%
U Value	1.03	1.05	1.02	1.05
UV Block	38%	99.9%	74.3%	99.9%
Total Solar Energy Rejected	19%	34%	41%	46%
Glare Reduction	NA	3%	NA	4%
Heat Loss Reduction	NA	0%	NA	-3%
Solar Heat Reduction	NA	18%	NA	8%

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

The information provided in this report is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.



3M is a trademark of 3M Company. © 3M 2016. All rights reserved.

*Will not interfere with cell phones, GPS systems or satellite radio. **IR for wavelength range of 900-1000nm.